

## PRODUCT FICHE TREO CS-12MF3

Model		Indoor Unit	CS-112MF3
		Outdoor Unit	CO-112MF3
Power Source		V/O/Hz	220-240 / 1 / 50
Capacity	Cooling	kW	3.52 (1.11 - 4.16)
	Heating		3.81 (1.08 - 4.22)
Power Input	Cooling	kW	1.20 (0.13 - 1.58)
	Heating		0.96 (0.10 - 1.58)
SEER	Cooling	W/W	6.1
SCOP	Heating		5.1
Energy Efficiency Class	Cooling		A++
	Heating		A+++
Current	Cooling	A	5.4 (0.5 - 6.9)
	Heating		4.2 (0.4 - 6.9)
<b>Indoor Unit</b>			
Air Flow		m <sup>3</sup> /h	600 / 500 / 360
Dimension	W × D × H	mm	805 × 194 × 285
Weight		kg	7.5
Sound Pressure Level		dB(A)	40 / 34 / 26 / 22
Sound Power Level		dB(A)	53
<b>Outdoor Unit</b>			
Air Flow		m <sup>3</sup> /h	1700
Dimension	W × D × H	mm	700 × 275 × 550
Weight		kg	22.7
Sound Pressure Level		dB(A)	56
Sound Power Level		dB(A)	65
Piping connection	Liquid side	mm	φ 6.35
	Gas side		φ 9.52
Max. refrigerant pipe		m	25
Max. difference in level			10
Operation range	Cooling	°C	-15 ~ 50
	Heating		-25 ~ 30
Refrigerant			R32