

PRODUCT FICHE TREO CS-24MF3

Model		Indoor Unit	CS-I24MF3
		Outdoor Unit	CO-I24MF3
Power Source		V/O/Hz	220-240 / 1 / 50
Capacity	Cooling	kW	7.03 (2.08 - 7.94)
	Heating		7.32 (1.61 - 8.79)
Power Input	Cooling	kW	2.34 (0.16 - 2.96)
	Heating		2.03 (0.26 - 3.14)
SEER	Cooling	W/W	6.1
SCOP	Heating		5.1
Energy Efficiency Class	Cooling		A++
	Heating		A+++
Current	Cooling	A	10.2 (0.7 - 13.3)
	Heating		10.2 (1.1 - 13.3)
Indoor Unit			
Air Flow		m ³ /h	980 / 817 / 662
Dimension	W × D × H	mm	1040 × 220 × 327
Weight		kg	12.3
Sound Pressure Level		dB(A)	44.5 / 42 / 34.5 / 28
Sound Power Level		dB(A)	59
Outdoor Unit			
Air Flow		m ³ /h	3000
Dimension	W × D × H	mm	845 × 363 × 702
Weight		kg	51.5
Sound Pressure Level		dB(A)	59.5
Sound Power Level		dB(A)	67
Piping connection	Liquid side	mm	φ 9.52
	Gas side		φ 15.9
Max. refrigerant pipe		m	50
Max. difference in level			25
Operation range	Cooling	°C	-15 ~ 50
	Heating		-25 ~ 30
Refrigerant			R32